

Allied Telesis AT-x510DP-52GTX Managed L3 Gigabit Ethernet (10/100/1000) 1U Black



Brand : Allied Telesis

Product code: 990-003848-00

Product name : AT-x510DP-52GTX

Stackable Gigabit Top of Rack Datacenter Switch with 48 x 10/100/1000T, 4 x 10G SFP+ ports, Dual Hot Swappable PSU, Back to Front Cooling

Allied Telesis AT-x510DP-52GTX Managed L3 Gigabit Ethernet (10/100/1000) 1U Black:

The Allied Telesis AT-x510DP-52GTX is the ideal Data Center Top-of-Rack (ToR) switch, featuring 48 x 10/100/1000T ports and 4 x 10G SFP+ uplink ports for high speed server and storage connectivity.

Dual hot-swappable load-sharing AC or DC power supplies with reverse airflow guarantee maximum uptime. Allied Telesis VCStack allows multiple units to be connected as a single virtual chassis, creating a highly resilient solution with no single point of failure that can even be distributed over long distances. The AT-x510DP-52GTX is the perfect choice for critical Data Center applications requiring uninterrupted service.

Management features		Security	
Switch type *	Managed	Access Control List (ACL)	✓
Switch layer	L3	IGMP snooping	✓
Quality of Service (QoS) support	✓	Multicast features	
Web-based management	✓	Multicast support	✓
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	48	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Stackable *	✓
Gigabit Ethernet (copper) ports quantity	48	Form factor	1U
SFP/SFP+ slots quantity	4	Product colour	Black
SFP module slots quantity	4	LED indicators	✓
Console port	RJ-45	Number of fans	1 fan(s)
Power connector	DC-in jack	Performance	
Network		Noise level	44 dB
Networking standards *	IEEE 802.1ab, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1v, IEEE 802.1x, IEEE 802.3, IEEE 802.3ac	Power	
	10G support *	Number of power supply units	1
	Copper ethernet cabling technology	AC input voltage	90 - 260 V
	Full duplex	AC input frequency	50 - 60 Hz
Head-of-line (HOL) blocking	✗	Power consumption (typical)	95 W
VLAN support	✓	Power over Ethernet (PoE)	
Number of VLANs	4000	Power over Ethernet (PoE) *	✗
Data transmission		Operational conditions	
Switching capacity *	176 Gbit/s	Operating temperature (T-T)	0 - 45 °C
MAC address table *	16000 entries	Storage temperature (T-T)	-25 - 70 °C
Latency (1 Gbps)	6.7 µs	Weight & dimensions	
Latency (10 Gbps)	4.9 µs	Width	440 mm
Security		Depth	480 mm
DHCP features	DHCP server, DHCP client	Height	44 mm
		Weight	5.7 kg
		Certificates	
		Certification	UL, cUL, TUV
		Logistics data	
		Harmonized System (HS) code	85176990



0767035199559



767035199559

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.