

Allied Telesis GS980M Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Grey



Brand : Allied Telesis

Product code: AT-GS980M/52PS-10

Product name : GS980M

48 10/100/1000T-POE+ switch with 4 SFP slots

Allied Telesis GS980M Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Grey:

Gigabit Layer 3 Lite Managed Switches

The Allied Telesis CentreCOM GS980M Series of Layer 3 Gigabit switches enable a cost-effective and fully managed network. A high-density, space saving solution, with Power over Ethernet (PoE+) to connect and power devices such as video surveillance cameras and IP phones, makes the GS980M Series ideal for applications at the network edge.

Allied Telesis GS980M. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. Full duplex. MAC address table: 16000 entries, Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet (PoE). Rack mounting, Form factor: 1U

Management features		Security	
Switch type *	Managed	Loop protection	✓
Switch layer	L3	BPDU filtering/protection	✓
Quality of Service (QoS) support	✓	Authentication	MAC-based authentication, Port-based authentication, Web-based authentication
Web-based management	✓	Password protection	✓
Configuring Location Settings (CLI)	✓	Authentication type	AAA, IEEE 802.1x, Network Access Control (NAC), RADIUS
System event log	✓		
MIB support	SNMP MIB		
Ports & interfaces		Multicast features	
Basic switching RJ-45 Ethernet ports quantity *	48	Multicast support	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Protocols	
SFP module slots quantity	4	Routing protocols	RIP, RIP-2
Network		Design	
Networking standards *	IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Rack mounting *	✓
10G support *	✗	Form factor	1U
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T	Product colour	Grey
Port mirroring	✓	Performance	
Full duplex	✓	Memory type	DDR-SDRAM
IP routing	✓	Internal memory	512 MB
Flow control support	✓	Flash memory	128 MB
Link aggregation	✓	Noise level	42 dB
Broadcast storm control	✓	Power	
Spanning tree protocol	✓	Power source *	AC
IPv4 routes	16	Power supply included *	✓
IPv6 routes	16	Power consumption (max)	48 W
VLAN support	✓	Power over Ethernet (PoE)	
Virtual LAN features	Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN	Power over Ethernet (PoE) *	✓
Number of VLANs	4094	Power over Ethernet (PoE) ports quantity	48
		Power over Ethernet plus (PoE+) ports quantity	24
		Power over Ethernet (PoE) power per port	48 W

Optical fiber		Power over Ethernet (PoE)	
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X	Total Power over Ethernet (PoE) budget	740 W
Data transmission		Operational conditions	
Switching capacity *	104 Gbit/s	Operating temperature (T-T)	0 - 50 °C
Forwarding rate	77.4 Mpps	Storage temperature (T-T)	-25 - 70 °C
MAC address table *	16000 entries	Operating relative humidity (H-H)	5 - 90%
Latency (10-100 Mbps)	6.8 µs	Storage relative humidity (H-H)	5 - 95%
Latency (1 Gbps)	3.8 µs	Operating altitude	0 - 3048 m
Static route	✓	Heat dissipation	164 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Packet buffer memory	3 MB	Width	441 mm
Security		Depth	359 mm
DHCP features	DHCP client, DHCP snooping	Height	44 mm
Access Control List (ACL)	✓	Weight	5.8 kg
IGMP snooping	✓	Packaging data	
Security algorithms	3DES, AES, MD5, PEAP, RSA, SHA-1, SHA-2, SNMP, SNMPv2, SNMPv3, SSH, SSH-2, SSL/TLS, TTLS	Package width	575 mm
		Package depth	520 mm
MAC address filtering	✓	Package height	150 mm
SSH/SSL support	✓	Package weight	7.8 kg



0767035215402



767035215402

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.