

ZYXEL

Zyxel GS1920-48V2 network switch Managed Gigabit Ethernet (10/100/1000) Black

Brand : Zyxel

Product code: GS1920-48V2

Product name : GS1920-48V2



- Inbuilt 'awareness' of other zyxel units in your network
- Web GUI interface for centralised management
- One-click remote factory resets and power cycling
- No additional software required

GS1920-48V2, 44x 1G RJ-45 PoE, 4x 1G RJ-45/SFP, 2x G SFP, 100 Gbps, 74 Mpps, 441x200x44.5 mm, GB Zyxel GS1920-48V2. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 44. MAC address table: 16000 entries, Switching capacity: 100 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack mounting



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Quality of Service (QoS) support	✓	Design	
ARP inspection	✓	Rack mounting *	✓
System event log	✓	Product colour	Black
MIB support	RFC 1066, RFC 1213, RFC 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011.2012,2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819,2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293	LED indicators	✓
		Safety	LVD, BSMI
Ports & interfaces		Electromagnetic compatibility	FCC 15 A, CE A, BSMI EMC
Basic switching RJ-45 Ethernet ports quantity *	44	Performance	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Internal memory	256 MB
Combo SFP ports quantity	4	Flash memory	32 MB
SFP module slots quantity	2	Noise level	26 dB
Fiber optic connector	SFP	Mean time between failures (MTBF)	672235 h
Network		Power	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
		Power consumption (max)	36.9 W
10G support *	✗	Power over Ethernet (PoE)	
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T	Power over Ethernet (PoE) *	✗
Flow control support	✓	Operational conditions	
Rate limiting	✓	Operating temperature (T-T)	0 - 50 °C
Spanning tree protocol	✓	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	10 - 95%
		Storage relative humidity (H-H)	10 - 95%
		Heat dissipation	125.83 BTU/h
		Weight & dimensions	
		Width	440 mm

Network		Weight & dimensions	
Virtual LAN features	Private VLAN, Voice VLAN, Protocol-based VLAN, MAC address-based VLAN, Port-based VLAN, IP subnet-based VLAN	Depth	220 mm
		Height	44.5 mm
		Weight	2.8 kg
Optical fiber		Packaging content	
Fiber ethernet cabling technology	1000BASE-X	Cables included	AC
Data transmission		Rack mount kit	✓
Security		Packaging data	
Switching capacity *	100 Gbit/s	Package width	496 mm
Forwarding rate	74 Mpps	Package depth	289 mm
MAC address table *	16000 entries	Package height	90 mm
Packet buffer memory	1.5 MB	Package weight	3.97 kg
Security		Certificates	
DHCP features	DHCP snooping, DHCP relay, DHCPv6 relay, DHCP client	Certification	RoHS
Access Control List (ACL)	✓	Logistics data	
IGMP snooping	✓	Harmonized System (HS) code	85176990
Security algorithms	802.1x RADIUS, SNMP, SNMPv3		
MAC address filtering	✓		
IP-MAC-Port binding	✓		
Authentication	Guest VLAN, Port-based authentication		
Password protection	✓		
Authentication type	IEEE 802.1x, RADIUS		
CPU defense	✓		
Queue scheduling algorithms	SPQ, WFQ, Weighted Round Robin (WRR)		



0760559125585



760559125585

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.