

Vertiv GXT5-3KL630RT2UXL uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 3000 W 4 AC outlet(s)

Brand : Vertiv

Product code: GXT5-3KL630RT2UXL

Product name : GXT5-3KL630RT2UXL



- Three-year comprehensive factory warranty for UPS and battery with next-day advanced exchange to support maximum availability
 - High power factor operation up to unity, allows for more connected devices
 - Energy Star® 2.0 certification; high efficiency in online (95%) and Active ECO (98%) modes
 - Enhanced local and remote management capabilities for intelligent critical infrastructure
- 3000W, 40 - 70 Hz, 2x L6-15R & 2x L6-20R, 208 VAC, Sinewave

Vertiv GXT5-3KL630RT2UXL uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 3000 W 4 AC outlet(s):

The Vertiv™ Liebert® GXT5-3KL630RT2UXL is an intelligent and efficient UPS solution which offers premium power outage protection and continuous power conditioning in a flexible rack/tower design. Ideally suited to protect critical infrastructure in both centralized and edge network applications, this UPS is easy to install, configure and operate. This single-phase UPS comes with L6-30P Input Cord. An optional Vertiv™ RDU101 SNMP/Webcard provides remote, SNMP and web UI-based monitoring.

Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at full load	3 min
Output power capacity *	3 kVA	Typical backup time at half load	9 min
Output power *	3000 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (max) *	280 V	Product colour *	Black
Input frequency *	40/70 Hz	Display type	LCD
Output operation voltage (min)	208 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Noise level	48 dB	Storage temperature (T-T)	-2 - 60 °C
Ports & interfaces		Operating relative humidity (H-H)	0 - 95%
AC outlet types	NEMA L6-15R, NEMA L6-30R	Operating altitude	0 - 3000 m
Power plug	NEMA L6-30P	Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Width	430 mm
		Depth	540 mm
		Height	85 mm
		Weight	29.6 kg



0767041026627



767041026627

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.