# DELL Pro P P2426H computer monitor 61 cm (24") 1920 x 1080 pixels Full HD LCD Black



**Brand :** DELL **Product family:** Pro P **Product code:** DELL-P2426H

**Product name :** Pro P P2426H

- 24" LCD IPS
- Full HD, 16:9, 1920 x 1080
- 120Hz, 5ms, 300cd/m²
- USB Hub

24", 1920 x 1080 Edge LED IPS, 120Hz, 16:9, 300cd/m², 5ms, 178°/178°

DELL Pro P P2426H computer monitor 61 cm (24") 1920 x 1080 pixels Full HD LCD Black:

Equipped for seamless productivity, this 23.8-inch FHD monitor offers extensive connectivity, high refresh rate and TÜV-certified 4-star eye comfort.
DELL Pro P P2426H. Display diagonal: 61 cm (24"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

| Display | |
|---|---|
| Display diagonal * | 61 cm (24") |
| Display resolution * | 1920 x 1080 pixels |
| HD type * | Full HD |
| Native aspect ratio * | 16:9 |
| Display technology * | LCD |
| Panel type * | IPS |
| LED backlight | ✔ |
| Backlight type | Edge LED |
| Touchscreen * | ✘ |
| Display brightness (typical) | 300 cd/m² |
| Response time * | 8 ms |
| Response time measurement type | GTG (Gray to Gray) |
| Anti-glare screen | ✔ |
| Screen shape * | Flat |
| Supported graphics resolutions | 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 720 (HD 720), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080) |
| Supported video modes | 1080p, 720p, 576p, 480p |
| Contrast ratio (typical) * | 1500:1 |
| Maximum refresh rate * | 120 Hz |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours * | 16.7 million colours |
| Response time (fast) | 5 ms |
| Pixel pitch | 0.2745 x 0.2745 mm |
| Pixel density | 93 ppi |
| Horizontal scan range | 30 - 135 kHz |
| Vertical scan range | 48 - 120 Hz |
| Viewable size, horizontal | 52.7 cm |
| Viewable size, vertical | 29.6 cm |

| Ergonomics | |
|---|---|
| Pivot | ✔ |
| Pivot angle | -90 - 90° |
| Swivelling | ✔ |
| Swivel angle range | -45 - 45° |
| Tilt adjustment | ✔ |
| Tilt angle range | -5 - 21° |
| On Screen Display (OSD) | ✔ |
| Plug and Play | ✔ |
| LED indicators | ✔ |

| Power | |
|---|---|
| Energy efficiency class (SDR) * | C |
| Energy efficiency class (HDR) * | Not available |
| Energy consumption (SDR) per 1000 hours * | 12 kWh |
| Power consumption (typical) * | 11.7 W |
| Power consumption (standby) * | 0.3 W |
| Power consumption (max) | 74 W |
| Power consumption (off) | 0.3 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50/60 Hz |
| Power supply type | Internal |
| Energy efficiency scale | A to G |

| Operational conditions | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 10 - 80% |
| Storage relative humidity (H-H) | 5 - 90% |
| Operating altitude | 0 - 5000 m |
| Non-operating altitude | 0 - 12192 m |

| Display | |
|---|---|
| Viewable size diagonal | 60.5 cm |
| Surface hardness | 3H |
| sRGB coverage (typical) | 99% |

| Performance | |
|---|---|
| NVIDIA G-SYNC * | ✕ |
| AMD FreeSync * | ✕ |
| Flicker-free technology | ✔ |

| Multimedia | |
|---|---|
| Built-in speaker(s) * | ✕ |
| Built-in camera * | ✕ |

| Design | |
|---|---|
| Product colour * | Black |

| Ports & interfaces | |
|---|---|
| Built-in USB hub * | ✔ |
| USB hub version | 2.0 / 3.2 Gen 1 (3.1 Gen 1) |
| USB upstream port type | USB Type-B |
| Number of downstream ports | 4 |
| Number of USB Type-B upstream ports quantity | 1 |
| USB Type-A downstream ports quantity | 2 |
| USB Type-C downstream ports quantity | 2 |
| HDMI * | ✔ |
| HDMI ports quantity | 1 |
| HDMI version | 1.4 |
| DisplayPorts quantity | 1 |
| DisplayPort version | 1.4 |
| Headphone out * | ✕ |
| HDCP | ✔ |
| HDCP version | 1.4 |
| Charging port type | USB Type-C |

| Ergonomics | |
|---|---|
| VESA mounting * | ✔ |
| Panel mounting interface | 100 x 100 mm |
| Cable management | ✔ |
| Cable lock slot * | ✔ |
| Cable lock slot type | Kensington |
| Height adjustment * | ✔ |
| Adjustable height (max) | 15 cm |

| Weight & dimensions | |
|---|---|
| Width (with stand) | 538.6 mm |
| Depth (with stand) | 181.8 mm |
| Height (with stand) | 410.8 mm |
| Weight (with stand) | 4.84 kg |
| Width (without stand) | 538.6 mm |
| Depth (without stand) | 50 mm |
| Height (without stand) | 314.2 mm |
| Weight (without stand) | 3.34 kg |
| Bezel width (side) | 5.8 mm |
| Bezel width (top) | 5.8 mm |
| Bezel width (bottom) | 1.2 cm |

| Packaging data | |
|---|---|
| Package weight | 6.66 kg |
| USB cable length | 1.8 m |

| Packaging content | |
|---|---|
| Stand included | ✔ |
| Cables included | DisplayPort, HDMI, USB Type-A to USB Type-B, AC |
| DisplayPort cable length | 1.8 m |
| HDMI cable length | 1.8 m |

| Sustainability | |
|---|---|
| Sustainability certificates | ENERGY STAR, TCO |
| Doesn't contain | PVC/BFR, Mercury, Arsenic |

| Carbon footprint | |
|---|---|
| Total carbon footprint (kg of CO2e) | 140 |
| Carbon emissions, manufacturing (kg of CO2e) | 67.48 |
| Carbon emissions, logistics (kg of CO2e) | 13.3 |
| Carbon emissions, energy usage (kg of CO2e) | 53.76 |
| Carbon emissions, end-of-life (kg of CO2e) | 5.32 |
| PAIA version | GaBi version 2, 2026 |

| Other features | |
|---|---|
| Compliance certificates | RoHS |

5397321029403

0884116692898

884116692898

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 28-AUG-2026. Prints or copies of Information are only valid on the printed Publication date